

Distributed by:



Kristian Electric Ltd.

Calgary
4215 64th Avenue SE
(403)292-9111

Edmonton
14236 121A Avenue
(780)444-6116

Saskatoon
710 46th Street E
(306)343-9111

www.kristian.ca

ELECTRIC CHAIN HOISTS



MODEL
SLC

SLC Shop Hoist

Coffing SLC Shop Hoist Models - Featuring rugged construction and high H4 duty cycle, this is the perfect hoist for around the shop or garage. This compact and job-proven hoist is ideal for commercial and industrial applications—lift up to 1000 pounds with 300 starts per hour. Put the SLC Shop Hoist to the test—it's UP for the task.

CAPACITIES & LIFT - Rated loads from 250 lb. to 1/2 Ton. 10 ft. lift standard.

VOLTAGES - 115 - single phase; 230/460, 575 - three phase, 60 hertz

SUSPENSION - Rigid top hook suspension prevents tangling of power cord.

POWER CORD - 6 1/2 ft. power cord with molded 3-prong plug on 115-volt units.

ALUMINUM HOUSING - Lightweight and compact to provide strength and portability

H4 DUTY CYCLE - 300 motor starts per hour

OVERLOAD DEVICE - Standard protector overload device protects against jamming and dangerous overloads.

LIFTWHEEL - 10-pocket oblique lay liftwheel provides longer chain wear.

GEAR TRAIN - Lifetime lubricated with non-oxidizing grease.

CHAIN - Alloy load chain (*zinc plated optional*).

H4 DUTY CYCLE - 300 motor starts per hour

ACCESSORIES & OPTIONS - Impact-resistant chain container available.

LIFETIME WARRANTY



250 - 1000 lb.

Made in USA

• SPECIFICATIONS •

SLC Models

Capacity (lb.)	Model Number	No. of Chains	Motor HP	Lifting Speed (FPM)	Headroom (in.)	Housing Dimensions (in)			Shipping Weight (lb.)
						H	W	L	
250	SLC0216	1	1/6	16	11 1/6	4 1/16	5 15/16	12 1/2	26
250	SLC0224	1	1/6	24	11 1/6	4 1/16	5 15/16	12 1/2	28
250	SLC0240	1	1/6	40	11 1/6	4 1/16	5 15/16	12 1/2	28
300	SLC0316	1	1/6	16	11 1/6	4 1/16	5 15/16	12 1/2	28
300	SLC0324	1	1/6	24	11 1/6	4 1/16	5 15/16	12 1/2	28
300	SLC0340	1	1/6	40	11 1/6	4 1/16	5 15/16	12 1/2	28
500	SLC0508	2	1/6	8	12 1/8	4 1/16	5 15/16	12 1/2	34
500	SLC0512	1	1/6	12	11 1/6	4 1/16	5 15/16	12 1/2	28
500	SLC0516	1	1/6	16	11 1/6	4 1/16	5 15/16	12 1/2	28
500	SLC0520	2	1/6	20	12 1/8	4 1/16	5 15/16	12 1/2	34
500	SLC0524	1	1/6	24	11 1/6	4 1/16	5 15/16	12 1/2	28
600	SLC0608	2	1/6	8	12 1/8	4 1/16	5 15/16	12 1/2	34
600	SLC0612	2	1/6	12	12 1/8	4 1/16	5 15/16	12 1/2	34
600	SLC0620	2	1/6	20	12 1/8	4 1/16	5 15/16	12 1/2	34
1000	SLC1006	2	1/6	6	12 1/8	4 1/16	5 15/16	12 1/2	34
1000	SLC1008	2	1/6	8	12 1/8	4 1/16	5 15/16	12 1/2	32
1000	SLC1012	2	1/6	12	12 1/8	4 1/16	5 15/16	12 1/2	32

Note: For complete dimensional data, refer to Coffing Dimensional Databook



ELECTRIC CHAIN HOISTS